



Wilson Agri Pasture Mat with Premium Pad Installation



1. Clear cow platform of any debris, including sharp edges, dirt & organic material.



2. Chalk a line on the platform at 4" (10cm) from the rear edge along the entire length.



3. Roll out top cover with reverse side up.



4. Be sure to leave a minimum of 6" (15cm) of extra top cover at each end.



5. Pull the top cover so it aligns along the chalk line.



6. Fasten one end of the Top Cover using plastic strips and a few nailins.



7. At the other end, stretch the top cover using a ratchet strap until the top cover is smooth and tight.



8. Go back to the first end and begin fastening down the top cover along the chalk line, using plastic strips and nailins (approximately 12" or 30cm apart).



9. Continue down the row until the row is completed.

10. Lay the mattresses in the stall. The back of the mattresses should be laying over the edge of the plastic strip.

11. Mattresses should be spaced at 46" (117cm) on centre, even when stall widths are wider (always install with the tag of the mattress to the front of the stall.) Leave 3" (7.5cm) at each end in order to later fasten top cover to the floor using plastic strips. If there is space left over at the final end, cut off the appropriate number of cells from the next mattress to fill the gap.

12. Install the premium pad with the back edge following the back edge of the mattress.



13. Cut the pad at the end of the row to match the end of the mattress. There will be an area of mattress at the front that will not be covered by the premium pad.



14. Lift Cover High and walk it forward to keep the mats in place.



15. Use ratchet straps or a commercial carpet stretcher to stretch the top cover. Stretch the cover tight over the mats.



16. Always start at the middle of the row and work out to the side to avoid wrinkles.



17. One top cover is tight, use plastic strip and nailins to hold it in place, using approximately 1 nailin for every 12" (30cm) of strip. Plastic strip is also used to fasten along each end of the mattress run

18. Top cover must be fastened down to the floor all around, do not fasten to any vertical surface.